



## MICHELIN® PILOT® SPORT

Drive your ultra-high performance car to new peaks of pleasure, thanks to this Z-speed-rated tire's powerful dry handling, extraordinary wet grip, and superb steering feedback. Swept-back grooves and advanced tread compounds deliver wet traction, while reinforced sidewalls and special rubber under the tread provide progressive, predictable cornering and tread stability under high torque.

### **Benefits**

Excellent comfort in a maximum performance tire



Extra long tread life in a maximum performance tire

# Michelin® Pilot® Sport

## UTQG RATING:

Treadwear	Traction	Temperature
220	AA	A

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Rev./Mile	Tread Depth (in/32nds)	Max Load (lbs @ psi)
205/55ZR16	91Y	RRBL	42803	5.5 - 7.5	8.4 on 6.5	24.9	834	10	1,356
205/50ZR16	87Y	RRBL	42807	5.5 - 7.5	8.2 on 5.5	24.1	861	10	1,201
225/55ZR16	95Y	RRBL	42822	6.0 - 8.0	9.2 on 7.0	25.8	806	10	1,521
225/50ZR16	92Y	RRBL	58082	6.0 - 8.0	9.2 on 7.0	24.9	833	10	1,389
245/50ZR16	98Y	RRBL	75587	7.0 - 8.5	9.7 on 7.5	25.8	805	10	1,653
255/50ZR16	100Y	RRBL	98973	7.0 - 9.0	10.2 on 8.0	26.0	799	10	1,764
215/45ZR16	86Y	RRBL	42809	7.0 - 8.0	8.4 on 7.0	23.7	874	10	1,168
225/45ZR16	89Y	RRBL	46436	7.0 - 8.5	8.9 on 7.5	23.8	872	10	1,279
245/45ZR16	94Y	RRBL	47003	7.5 - 9.0	9.9 on 8.0	24.7	840	10	1,477
205/50ZR17	89Y	RRBL	78824	5.5 - 7.5	8.1 on 6.5	25.1	826	10	1,279
205/50ZR17 1 "N2"	98Y	RRBL	72151	5.5 - 7.5	8.1 on 6.5	25.1	826	10	1,279
215/45ZR17	87Y	RRBL	63643	7.0 - 8.0	8.2 on 7.0	24.7	841	10	1,201
225/45ZR17 1 "B"	91Y	RRBL	42406	7.0 - 8.5	8.8 on 7.5	24.8	837	10	1,356
225/45ZR17	91Y	RRBL	73761	7.0 - 8.5	8.8 on 7.5	24.8	837	10	1,356
225/45ZR17	91Y	RRBL	75303	7.0 - 8.5	8.8 on 7.5	24.8	837	10	1,356
225/45ZR17 "MO"	91Y	RRBL	91857						
235/45ZR17	94Y	RRBL	66104	7.5 - 8.0	9.3 on 8.0	25.2	822	10	1,477
245/45ZR17	95Y	RRBL	64437	7.5 - 9.0	9.7 on 8.0	25.7	806	10	1,521
255/45ZR17	98Y	RRBL	50510	8.0 - 9.5	10.1 on 8.5	26.0	798	10	1,653
255/45ZR17 "G1"	98W	RRBL	87308						
215/40ZR17	83Y	RRBL	69201	7.0 - 8.5	8.3 on 7.5	23.8	872	10	1,074
235/40ZR17	90Y	RRBL	77306	8.0 - 9.5	9.4 on 8.5	24.4	849	10	1,323
245/40ZR17	91Y	RRBL	68849	8.0 - 9.5	9.6 on 8.5	24.7	841	10	1,356
245/40ZR17	91Y	RRBL	50985						
255/40ZR17	94Y	RRBL	75349	8.5 - 10.0	10.2 on 9.0	25.1	827	10	1,477
255/40ZR17 1 "N2"	94Y	RRBL	89297	8.5 - 10.0	10.2 on 9.0	25.1	827	10	1,477
275/40ZR17	98Y	RRBL	42847	9.0 - 11.0	11.0 on 9.5	25.7	809	10	1,653
285/40ZR17	100Y	RRBL	58261	9.5 - 11.0	11.5 on 10.0	26.0	797	10	1,764
265/35ZR17	92Y	RRBL	43817	9.0 - 10.5	9.7 on 9.0	24.4	854	10	1,356
315/35ZR17	102Y	RRBL	99884	10.5 - 12.5	12.6 on 11.0	25.7	808	10	1,874
335/35ZR17	106Y	RRBL	57315	11.0 - 13.0	13.7 on 12.0	26.0	797	10	2,094
235/50ZR18	97Y	RRBL	43648	6.5 - 8.5	9.5 on 7.5	27.7	762	10	1,609
215/45ZR18 "K1"	89Y	RRBL	60302	7.0 - 8.0	8.1 on 7.0	25.6	811	10	1,279
225/45ZR18	91Y	RRBL	51137	7.0 - 8.5	8.8 on 7.5	25.8	804	10	1,356
225/45ZR18	91W	RRBL	94600						
245/45ZR18	96Y	RRBL	41075	7.5 - 9.0	9.6 on 8.0	26.8	775	10	1,565
245/45ZR18	96W	RRBL	61632						
255/45ZR18	99Y	RRBL	66279	8.0 - 9.5	10.3 on 8.5	26.9	771	10	1,709
225/40ZR18 1	88Y	RRBL	86523	7.5 - 9.0	8.9 on 8.0	25.3	821	10	1,235
225/40ZR18 "N0"	88Y	RRBL	70149	7.5 - 9.0	8.9 on 8.0	25.3	821	10	1,235
225/40ZR18 1 "N1"		RRBL	99587						
235/40ZR18	91Y	RRBL	91376	8.0 - 9.5	9.5 on 8.5	25.4	816	10	1,356
245/40ZR18	93Y	RRBL	98279	8.0 - 9.5	9.7 on 8.5	25.8	805	10	1,433
255/40ZR18	95Y	RRBL	49693	8.5 - 9.0	10.2 on 9.0	25.9	803	10	1,521
255/40ZR18 "G1"	95Y	RRBL	46485						
265/40ZR18 "MO"	97Y	RRBL	73432						
275/40ZR18 "K1"	99Y	RRBL	83979	9.0 - 11.0	11.0 on 9.5	26.8	776	10	1,709
275/40ZR18	99Y	RRBL	41695	9.0 - 11.0	11.0 on 9.5	26.8	776	10	1,709
235/35ZR18	86Y	RRBL	60265	8.0 - 9.5	9.5 on 8.5	24.4	850	10	1,168
255/35ZR18 REINF	94Y	RRBL	72911						
255/35ZR18	90Y	RRBL	50581						
265/35ZR18	93Y	RRBL	67916	9.0 - 10.5	10.5 on 9.5	25.3	819	10	1,433
265/35ZR18 1 "N1"		RRBL	64854						
275/35ZR18	95Y	RRBL	47418	9.0 - 11.0	10.7 on 9.5	25.7	807	10	1,521
275/35ZR18 "C1"	93Y	RRBL	59151	9.0 - 11.0	10.7 on 9.5	25.7	812	9	1,521
P275/35ZR18 "ZP"	87Y	RRBL	42196						
285/35ZR18	97Y	RRBL	82982	9.5 - 11.0	11.3 on 10.0	26.0	800	10	1,609
285/35ZR18 "MO"	97Y	RRBL	59692						
295/35ZR18	99Y	RRBL	98290	10.0 - 11.5	11.7 on 10.5	26.2	793	10	1,709
345/35ZR18	109Y	RRBL	73970	11.5 - 13.5	13.9 on 12.0	27.4	758	10	2,271
285/30ZR18 "N0"	93Y	RRBL	95191	10.0 - 11.0	11.3 on 10.0	25.0	832	10	1,433
285/30ZR18 1 "N1"		RRBL	72189						
315/30ZR18 1 "N0"	98Y	RRBL	40822						
335/30ZR18	102Y	RRBL	72458	12.0 - 13.0	13.3 on 12.0	26.1	795	10	1,874
335/30ZR18 "C1"	102Y	RRBL	75959	12.0 - 13.0	13.3 on 12.0	26.1	803	9	1,874
225/40ZR19		RRBL	77216						
255/40ZR19	96Y	RRBL	67043	8.5 - 10.0	10.1 on 9.0	27.0	770	10	1,565
235/35ZR19 "EL"		RRBL	92749						
245/35ZR19 REINF	93Y	RRBL	89331	8.0 - 9.5	9.5 on 8.5	25.8	806	10	1,279
255/35ZR19		RRBL	44068						
295/35ZR19	100Y	RRBL	79717	10.0 - 11.5	11.8 on 10.5	27.2	764	10	1,764
265/30ZR19 "EL"		RRBL	54418						
P345/30ZR19 "ZP"	98Y	RRBL	95380						
245/40ZR20	95Y	RRBL	44350	8.0 - 9.5	9.8 on 8.5	27.6	753	10	1,521
275/35ZR20	98Y	RRBL	62122	9.0 - 11.0	10.9 on 9.5	27.6	753	10	1,653
285/30ZR20	95Y	RRBL	43251						
255/35ZR21 "M1"		RRBL	89252						
295/30ZR21 "M1"		RRBL	52915						



# Michelin® Pilot® Sport

## UTQG RATING:

Treadwear	Traction	Temperature
220	AA	A

Michelin® tires and tubes are subject to a continuous development program. Michelin North America (Canada), Inc. reserves the right to change product specifications at any time without notice or obligation.

1. The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.

2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width. **WARNING:** Serious or fatal injury may result from improper mounting, from under-inflation/over-inflation/over-loading or from tire damage due to abusive use. For proper mounting, see tire dealer. For proper tire size and inflation pressure, consult Tire Information Placard in vehicle.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual. For speeds over 160 km/h (100 mph), load and inflation must be adjusted according to the table below.

Maximum Speed (km/h)	160	170	180	190
Inflation Increase (psi)	0	1	2	3
Load Capacity (% of max.)	100	100	100	100

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

**Powerful wet traction, handling, and braking with progressive, driver-friendly dry handling** thanks to Advanced Technology tread rubber compounds.

**Outstanding wet traction and reduced tire noise on dry roads** is provided by these radically swept-back lateral grooves.

**Stabilized tread in high torque applications** due to high modulus undertread.

**Sharpened steering response and feedback for exceptionally faithful, communicative road feel** is delivered by this continuous center rib and elongated rolling footprint.

**Quicker response, improved ride compliance, and superior damping of noise and vibration** because of high-tensile, low-mass steel cords and belts.

**Resistance to centrifugal distortion, optimizing high-speed handling and durability** provided by size-optimized BAZ Technology™ (spiral-wrapped nylon Banded At Zero Degrees to tire rotation).

**Steering feedback is better matched with steering response** thanks to a special high-hysteresis compound that surrounds the bead area.

**Powerful, predictable cornering** thanks to rayon casing with ultra-reinforced sidewalls and lightweight rim protectors.

**Maintaining the ideal shape of a running tire while facilitating easy mounting** is what these wound cable beads and specially-designed bead seating area were designed for.

